

Two-way differential strategy for wireless sensor networks

Samer Alabed¹, Amer Alsaraira¹, Nour Mostafa², Mohammad Al-Rabayah², Ahmed Shdefat²,
Chamseddine Zaki², Omar A. Saraereh³, Zakwan Al-Arnaout²

¹Department of Biomedical Engineering, School of Applied Medical Sciences, German Jordanian University, Amman, Jordan

²College of Engineering and Technology, American University of the Middle East, Egaila, Kuwait

³Department of Electrical Engineering, Faculty of Engineering, Hashemite University, Zarqa, Jordan

Article Info

Article history:

Received Mar 1, 2023

Revised Apr 14, 2023

Accepted Jun 5, 2023

Keywords:

Beamforming technique

Diversity techniques

Non-coherent techniques


Space-time coding

Wireless sensor networks

ABSTRACT

In this paper, a novel optimal two-way amplify and forward (AF) differential beamforming method for wireless sensor network is proposed. The proposed method is an advanced signal processing technique used to enhance the performance and reliability of the communication link by exploiting the diversity provided by multiple antennas. Unlike current state-of-the-art methods which require the knowledge of channel state information (CSI) at both transmitting and receiving antennas or at least at the receiving antennas, the suggested method does not need CSI at any transmitting or receiving antenna. Moreover, the proposed method enjoys high error performance with high diversity and coding gain and has a very low encoding and decoding complexity. Through our simulations, the proposed method is proved to outperform the best known non-coherent multi-antenna methods.

This is an open access article under the [CC BY-SA](#) license.



Corresponding Author:

Samer J. Alabed

Department of Biomedical Engineering, School of Applied Medical Sciences

German Jordanian University

Amman, 11180 Jordan

Email: samer.alabed@gju.edu.jo

1. INTRODUCTION

In future communication networks, increasing data rate while maintaining an acceptable error rate is one of the main goals to be achieved. Other factors are also considered while optimizing the system performance such as delay, encoding and decoding complexity, and network coverage. On the other hand, the system performance of these networks can be impacted by different factors such as multipath fading and interference. These factors limit the throughput and reduce the error performance [1]–[10]. Several spatial diversity methods have been suggested to eliminate the aforementioned impairments, e.g., relay selection methods [5], [7], beamforming methods [11], [12], and space-time coding (STC) methods [10], [13]–[20]. Recently, distributed spatial diversity methods for cooperative communication networks have been suggested to increase the overall throughput and network coverage, and to reduce the effects of these channel impairments [21]–[25]. Those methods can remarkably improve the performance of wireless relaying systems by increasing the data rate and reducing the bit-error rate (BER). Also, receiving different versions of the transmitted signal via various relays with different amplitudes and phases increases the system diversity. In particular, applying efficient techniques to combine the various received signals could lead to a remarkable improvement in system performance.

The relay node, as an intermediate point that: i) obtains the signal through the source-node link, ii) processes the signal, and iii) transmits the signal to the receiver-node. Many processing protocols could be applied at the relay such as amplify and forward (AF) protocol, combine and forward (CF) protocol, and decode and forward (DF) protocol. These techniques enhance the obtained signal to noise ratio (SNR),

throughput, and the performance in terms of BER, however different level of complexity is associated with each technique. Therefore, complexity-performance tradeoff is a major concern in such systems that requires to be optimized along with the number of deployed relays. Intuitively, increasing the number of relays distributed between the source and the destination improve the overall system performance in terms of BER and throughput [26]–[32]. Several spatial-diversity methods have been recently suggested considering that the channel state information (CSI) is available at every node in the whole system [5], [7]. In these methods, a slow fading channel model is considered. However, other methods assume that CSI is only available at the destination [8], [17]–[19]. Unlike the previous methods, both blind and differential diversity methods [10], [11], [13]–[15], [22]–[25] provide an increase in the diversity gain without the need to have the CSI at any transmitting or receiving nodes. Unfortunately, the latter methods suffer from several issues such as low error performance, large delay, and low throughput when compared to other methods.

Recently, two-directional communication techniques have been suggested as a way to enhance the overall error performance and achievable data rate [6], [10], [14]. Two-directional techniques are categorized according to the number of phases required for the terminals to exchange their data into two-phase [10], three-phase [6], and four-phase [11] protocols. Note that the number of phases required to exchange the information highly affect the overall performance and the achievable data rate. Moreover, the relay nodes distributed randomly between the terminals are utilized to process and forward the data using a certain coding scheme. The relay nodes can process and encode the received signals using orthogonal, e.g., STC, or non-orthogonal coding techniques. STC is considered as an efficient way to send the information symbols during several phases and using several relay nodes to achieve high performance in terms of BER and high data rate with low encoding and decoding complexity [10], [14]. Non-orthogonal schemes have high diversity and coding gain. However, these schemes suffer from very high decoding complexity which increases exponentially with the number of relay nodes or constellation size in some cases, especially due to channel estimation. Recently, several distributed special diversity schemes have been suggested to offer full diversity and high coding gain without needing CSI at any node in the whole network to reduce the overall encoding and decoding complexity and overhead due to channel estimation [10], [11], [13]–[15], [22]–[25]. More recent techniques and types related to wireless relay and sensor networks have been studied [33]–[37].

In this paper, a novel technique for wireless relay networks is proposed and verified via mathematical analysis and numerical simulations. Unlike current state-of-the-art research where it is assumed that CSI is available at both transmitter-and-receiver or only at the receiver, the proposed technique does not require any CSI neither at transmitter nor at the receiver. The proposed technique for wireless relay network has shown a remarkable improvement in the system's performance compared to existing systems in terms of BER. This paper is organized as follows: in section 2 the system model is discussed and detailed mathematical analysis is provided. In section 3, numerical analysis and results are provided showing the performance improvements. In section 4, conclusion and future directions are investigated.

2. METHOD

In this work, a novel optimal bi-directional AF multi-antenna method for wireless sensor network is proposed. Unlike current state-of-the-art methods which require the channel knowledge at both transmitting and receiving antennas or at least at the receiving antennas, the proposed method does not require channel knowledge at any antenna. Moreover, the proposed method enjoys high error performance with high diversity and coding gain, and has a very low encoding and decoding complexity.

2.1. System model

The communication system model is shown in Figure 1. It consists of two transmitting nodes τ_1 and τ_2 that are communicating in a half-duplex mode in the presence of R intermediate relays denoted as $\mathcal{R}_1, \mathcal{R}_2, \dots, \mathcal{R}_R$. It is assumed that there is no direct link between the two transmitting nodes. Moreover, each intermediate relay \mathcal{R}_i has a single antenna that is utilized for both transmission and reception. The relays can only communicate through the transmitting nodes, and they do not share the received data symbols internally. Let $x_{\tau_1}^{(i)}$ and $x_{\tau_2}^{(i)}$ be the transmitted symbols by terminal-1 (τ_1) and terminal-2 (τ_2) respectively, where i represents the transmission time slot index. The channel coefficients between τ_1 and the R relays are given by the vector $f \in \mathbb{C}^{R \times 1}$ where $f = (f_1, f_2, \dots, f_R)$ and f_i represents the channel coefficient between τ_1 and i^{th} relay \mathcal{R}_i . Similarly, the channel coefficients between τ_2 and the R relays are given by the vector $g \in \mathbb{C}^{R \times 1}$ where $g = (g_1, g_2, \dots, g_R)$ and g_i represents the channel coefficient between τ_2 and i^{th} relay \mathcal{R}_i . Let $y_{R1}^{(i)}$ and $y_{R2}^{(i)}$ be the vectors received by an intermediate relay from the first and the second transmitters respectively which are given as (1) and (2):

$$y_{R_1}^{(i)} = \sqrt{P_{\tau_1}} f x_{\tau_1}^{(i)} + n_{R_1}^{(i)} \quad (1)$$

$$y_{R_2}^{(i)} = \sqrt{P_{\tau_2}} g x_{\tau_2}^{(i)} + n_{R_2}^{(i)} \quad (2)$$

where P_{τ_1} and P_{τ_2} are the transmitted power of terminal-1 (τ_1) and terminal-2 (τ_2), respectively and the relay noise vectors $n_{R_1}^{(i)}$, $n_{R_2}^{(i)}$ have a circularly symmetric Gaussian distribution with variance σ^2 . Let $y_{\tau_1}^{(i)}$ represents the received signal at terminal-1 from all relays and $y_{\tau_2}^{(i)}$ represents the received signal at terminal-2 from all relays, then:

$$y_{\tau_1}^{(i)} = \sqrt{P_R} f^T x_{R_1}^{(i)} + n_{\tau_1}^{(i)} \quad (3)$$

$$y_{\tau_2}^{(i)} = \sqrt{P_R} g^T x_{R_2}^{(i)} + n_{\tau_2}^{(i)} \quad (4)$$

where P_R defines the relays transmitting power, $x_{R_1}^{(i)}$ and $x_{R_2}^{(i)}$ define symbol vectors retransmitted by relays to terminal-1 and terminal-2 correspondingly, and the node noise $n_{\tau_1}^{(i)}$ and $n_{\tau_2}^{(i)}$ have a circularly symmetric Gaussian distribution with variance σ^2 . The channel vectors f and g follow the same Gaussian distribution with unity variance.




Figure 1. System model

2.1.1. Distributed differential space time coding

In this system, it is assumed that there is no CSI at either nodes or relays and the differential technique for two-way communication [9]–[15] is considered for signal transmission. The transmission scheme is arranged in terms of blocks in time domain and during this interval, each node transmits $T=R$ symbols. In particular, let us define $s_{\tau_1}^{(i)}$ and $s_{\tau_2}^{(i)}$ as the symbol vectors to be transmitted in i^{th} block as (5):

$$s_{\tau_1}^{(i)} = [s_{\tau_1,1}^{(i)} \quad \dots \quad s_{\tau_1,T}^{(i)}]^T, s_{\tau_2}^{(i)} = [s_{\tau_2,1}^{(i)} \quad \dots \quad s_{\tau_2,T}^{(i)}]^T \quad (5)$$

Also define the differentially encoded vectors $x_{\tau_1}^{(i)}$ and $x_{\tau_2}^{(i)}$ as (6):

$$x_{\tau_1}^{(i)} = \text{diag}(x_{\tau_1}^{(i-1)}) s_{\tau_1}^{(i)}, x_{\tau_2}^{(i)} = \text{diag}(x_{\tau_2}^{(i-1)}) s_{\tau_2}^{(i)} \quad (6)$$

where $\text{diag}(\ast)$ is a function that takes T elements and generates a T by T diagonal matrix. The symbol vectors received during i^{th} block by r^{th} array are then defined as (7):

$$y_{R_1,r}^{(i)} = \sqrt{P_{\tau_1}} f_r x_{\tau_1}^{(i)} + n_{R_1,r}^{(i)}, y_{R_2,r}^{(i)} = \sqrt{P_{\tau_2}} g_r x_{\tau_2}^{(i)} + n_{R_2,r}^{(i)} \quad (7)$$

Consider the operator $\Phi_{R,r}^{(i)}$ that is used to perform a transformation for the vectors $y_{R_1,r}^{(i)}$ and $y_{R_2,r}^{(i)}$ as (8):

$$y_{R,r}^{(i)} = \Phi_{R,r}^{(i)} (y_{R_1,r}^{(i)} \odot y_{R_2,r}^{(i)}) \quad (8)$$

where \odot stands for kronecker product and $\Phi_{R,r}^{(i)}$ is a power scaling matrix of diagonal form that is defined as (9):

$$\Phi_{R,r}^{(i)} = \text{diag}(|y_{R1,r}^{(i)} \odot y_{R2,r}^{(i)}|)^{-1} \quad (9)$$

i.e. $\Phi_{R,r}^{(i)}$ ensures equal power elements in $y_{R,r}^{(i)}$. Consider the following relation in terms of the input signal where $x_R^{(i)} = x_{\tau_1}^{(i)} \odot x_{\tau_2}^{(i)}$. Recalling the above procedure, then the received signal could be written as (10):

$$y_{R,r}^{(i)} = \Phi_{R,r}^{(i)} (\sqrt{P_{\tau_1} P_{\tau_2}} f_r g_r x_R^{(i)} + n_{R,r}^{(i)}) \quad (10)$$

where $n_{R,r}^{(i)}$ is a corresponding noise term. Now, let us use space-time block code methodology in reformulating the problem from relays transmission perspective for the vectors $y_{R,r}^{(i)}$. Therefore, we define a space time code structure by a set of permutation matrices A_1, \dots, A_T and B_1, \dots, B_T . Then, restrict possible codes to ones, for which permutation matrices possess mutual exclusivity property i.e., either $A_i=0$ or $B_i=0$. After that, we define code matrix of r^{th} relay $X_{R,r}^{(i)} \in \mathbb{C}^{T \times R}$ corresponding to the vector received at r^{th} relay $y_{R,r}^{(i)}$. This code matrix formation can then be represented by applying operator χ :

$$X_{R,r}^{(i)} = \chi(y_{R,r}^{(i)}) = [A_1 y_{R,r}^{(i)} + B_1 y_{R,r}^{(i)} \quad \dots \quad A_T y_{R,r}^{(i)} + B_T y_{R,r}^{(i)}]^T \quad (11)$$

Let then each relay R transmit r^{th} column of its correspondent code matrix $X_{R,r}^{(i)}$. Signal vector received at second node $y_{\tau_2}^{(i)}$ can then be then written as (12):

$$\begin{aligned} y_{\tau_2}^{(i)} &= X_R^{(i)} \Delta_g^{(i)} \Delta_f^{(i)} g + n_{\tau_2}^{(i)} \\ &= (S_{\tau_1}^{(i)} \odot S_{\tau_2}^{(i)} \odot X_{\tau_1}^{(i-1)} \odot X_{\tau_2}^{(i-1)}) \Delta_g^{(i)} \Delta_f^{(i)} g + n_{\tau_2}^{(i)} \\ &= (S_{\tau_1}^{(i)} \odot S_{\tau_2}^{(i)} \odot X_R^{(i-1)}) \Delta_g^{(i)} \Delta_f^{(i)} g \end{aligned} \quad (12)$$

where,

$$X_R^{(i)} = \chi(x_R^{(i)}), S_{\tau_1}^{(i)} = \chi(s_{\tau_1}^{(i)}), S_{\tau_2}^{(i)} = \chi(s_{\tau_2}^{(i)}), X_{\tau_1}^{(i-1)} = \chi(x_{\tau_1}^{(i-1)}), X_{\tau_2}^{(i-1)} = \chi(x_{\tau_2}^{(i-1)}) \quad (13)$$

$\Delta_g^{(i)}$ and $\Delta_f^{(i)}$ being diagonal matrices defined as (14) and (15):

$$\Delta_{g,kk}^{(i)} = \begin{cases} \exp(j\angle g_k), & \text{if } B_i = 0 \\ \exp(-j\angle g_k), & \text{if } A_i = 0 \end{cases} \quad (14)$$

$$\Delta_{f,kk}^{(i)} = \begin{cases} \exp(j\angle f_k), & \text{if } B_i = 0 \\ \exp(-j\angle f_k), & \text{if } A_i = 0 \end{cases} \quad (15)$$

Now, decoding of $s_{\tau_1}^{(i)}$ can then be performed using (16):

$$s_{\tau_1}^{(i)} = \underset{s_{\tau_1}^{(i)}}{\text{argmin}} \left\| y_{\tau_2}^{(i)} - (S_{\tau_1}^{(i)} \odot S_{\tau_2}^{(i)} \odot \hat{X}_R^{(i-1)}) \hat{X}_R^{(i-1)-1} y_{\tau_2}^{(i-1)} \right\| \quad (16)$$

Similarly, an estimate for $s_{\tau_2}^{(i)}$ is obtained.

2.1.2. Simple distributed differential beamforming

This scheme performs transmission in four time slots [11], [24]. We start by defining symbols transmitted by first and second relays $x_{\tau_1}^{(i)}$ and $x_{\tau_2}^{(i)}$ as differentially encoded as (17):

$$x_{\tau_1}^{(i)} = x_{\tau_1}^{(i-1)} s_{\tau_1}^{(i)}, x_{\tau_2}^{(i)} = x_{\tau_2}^{(i-1)} s_{\tau_2}^{(i)} \quad (17)$$

Now, define the signals received by the r^{th} relay from the first terminal in i^{th} and $(i-1)^{\text{th}}$ blocks as $y_{R1,r}^{(i)}, y_{R1,r}^{(i-1)}$, and similarly from the second node as $y_{R2,r}^{(i)}$ and $y_{R2,r}^{(i-1)}$ respectively. In this analysis, M-phase shift keying

(M-PSK) is considered for transmission. Then, the definition of the signals transmitted by the r -th relay $x_{R1,r}^{(i)}$ and $x_{R2,r}^{(i)}$ as (18) and (19):

$$x_{R1,r}^{(i)} = \sqrt{P_R} \exp(-j\alpha y_{R1,r}^{(i)} - j\alpha y_{R2,r}^{(i-1)} + j\alpha y_{R2,r}^{(i)}) \quad (18)$$

$$x_{R2,r}^{(i)} = \sqrt{P_R} \exp(-j\alpha y_{R2,r}^{(i)} - j\alpha y_{R1,r}^{(i-1)} + j\alpha y_{R1,r}^{(i)}) \quad (19)$$

The same precoding procedure is performed at all relays. Hence, the estimated symbols at terminal nodes can be calculated using as (20) and (21):

$$\hat{s}_{\tau_2}^{(i)} = \underset{\hat{s}_{\tau_2}^{(i)}}{\operatorname{argmin}} \left| \exp(j\alpha y_{\tau_1}^{(i)}) - \exp \left(j(\alpha y_{\tau_1}^{(i-1)} - \alpha \hat{s}_{\tau_1}^{(i)} - \alpha \hat{s}_{\tau_2}^{(i-1)} + \alpha \hat{s}_{\tau_2}^{(i)}) \right) \right| \quad (20)$$

$$\hat{s}_{\tau_1}^{(i)} = \underset{\hat{s}_{\tau_1}^{(i)}}{\operatorname{argmin}} \left| \exp(j\alpha y_{\tau_2}^{(i)}) - \exp \left(j(\alpha y_{\tau_2}^{(i-1)} + \alpha \hat{s}_{\tau_2}^{(i)} + \alpha \hat{s}_{\tau_1}^{(i-1)} + \alpha \hat{s}_{\tau_1}^{(i)}) \right) \right| \quad (21)$$

2.1.3. General rank beamformer (GRB)

Suppose now for vectors f and g known covariance matrices are R_{ff} and R_{gg} . Define filter matrices Φ_{τ_1} and Φ_{τ_2} to maximize the SNR at the receivers [12]. Introduce supplementary vectors w_d and w_u :

$$w_d = \sqrt{\frac{P_T}{(1+\lambda_{\max})v^H R_{nn} v}} u, w_u = v \quad (22)$$

where v is a normalized eigenvector of $R_{nn}^{-1} R_{ff}$ for maximum eigenvalue λ_{\max} and u is principal eigenvector of R_{gg} . Matrices Φ_{τ_1} and Φ_{τ_2} are then defined as (23):

$$\Phi_{\tau_2} = w_d w_u^H, \Phi_{\tau_1} = w_u^* w_d^T \quad (23)$$

2.1.4. The proposed differential beamforming scheme using maximum ratio combining

Now, suppose that relays are able to exchange received data symbols. This can be thought as a substitution of single antenna relay array of size R by a single relay with R antennas. Assume using AF approach, i.e., relay does not decode received symbols. Relay performs array processing of multiplying by matrices Φ_{τ_1} and Φ_{τ_2} . Then received signals at first and second nodes are defined as (24):

$$y_{\tau_1}^{(i)} = \Phi_{\tau_1} y_{R1}^{(i)} + n_{\tau_1}^{(i)}, y_{\tau_2}^{(i)} = \Phi_{\tau_2} y_{R2}^{(i)} + n_{\tau_2}^{(i)} \quad (24)$$

Using maximum ratio combining (MRC) approach Φ_{τ_1} and Φ_{τ_2} are to be defined as (25):

$$y_{\tau_1}^{(i)} = \Phi_{\tau_1} y_{R1}^{(i)} + n_{\tau_1}^{(i)}, y_{\tau_2}^{(i)} = \Phi_{\tau_2} y_{R2}^{(i)} + n_{\tau_2}^{(i)} \quad (25)$$

Decoding at receivers then can be performed using (25).

3. RESULTS AND DISCUSSION

In this section, we introduce the simulation results of the system model discussed in section 2. Figures 2 and 3 show the BER versus the SNR of a cooperative communication system composed of two terminals τ_1 and τ_2 and two relay nodes ($R=2$). In our simulations, Rayleigh flat-fading channels are considered, and the transmission was simulated for 10^5 channel realizations. For each channel realization 48 time slots were simulated. In the transmission from τ_1 to τ_2 , the total transmitted power is divided equally among the source terminal P_{τ_1} and the relay node P_r such that $P_{\tau_1} = P_r$ where the total relay power P_R is also equally divided among all its transmitting antennas. For Figure 2, 16-PSK modulation was used for four phase schemes such as simple distributed differential beamforming scheme, differential MRC scheme, and GRB scheme. For the three phase schemes such as differential space time coding scheme 8-PSK modulation was used to equalize spectral efficiency. For the two-phase schemes such as differential space time coding scheme [10], 4-PSK modulation was used to equalize spectral efficiency. The AF protocol is performed using one bit per channel use (bpcu).

By inspecting Figure 2, the BER performance ranking of the schemes explained in section 2 from the worst to the best will be, differential space time coding scheme explained in subsubsection 2.1.1 has the worst performance, then GRB scheme explained in subsubsection 2.1.3, followed by simple distributed differential beamforming scheme explained in subsubsection 2.1.2 and finally the proposed differential MRC scheme explained in subsubsection 2.1.4, where MRC scheme has a superior performance. This is due to the fact that MRC scheme allows received symbol exchange between individual relays. GRB scheme has the best performance in low SNR region, due to the knowledge of correlation properties of channels and received symbol exchange between relays. At high SNR region, differential MRC scheme however, has a better performance, due to instantaneous channel information usage.




Figure 2. Performance comparison for relay transmission schemes using the AF protocol with 1 bpcu and $R=2$

In Figure 3 the suggested scheme explained in subsubsection 2.1.4 is compared to the state-of-the-art coherent and non-coherent schemes suggested in [10]–[14] using the AF protocol and two bpcu. Figure 3 clearly shows that the performance of the suggested scheme outperforms the best known two-there and four-phase distributed space time coding schemes suggested in [10], [13], [14], as well as the distributed beamforming schemes suggested in [11], [12]. Note that the diversity gain is related to the slope of the BER curve at high SNR values while the coding gain is related to the shift of the BER curve to the left, e.g., by doubling the power, the BER curve will be shifted 3 dB to the left without any change to the slope of the BER curve which means that the added coding gain is 3 dB in this case. From Figure 3, we can observe that the proposed method is steeper and shifted horizontally more to the left than the other methods. This is why the proposed method has high diversity and coding gain.




Figure 3. Performance comparison for relay transmission schemes using the AF protocol with 2 bpcu and $R=2$

In Figure 4 the proposed method suggested in subsubsection 2.1.4 is compared with the state-of-the-art coherent and non-coherent methods suggested in [10], [12]–[14], [33], [36] using the AF protocol and one bpcu. Figure 4 clearly shows that the performance of the proposed method outperforms the best known two-there and four-phase distributed space time coding schemes proposed in [10], [13], [14], [33], as well as the distributed beamforming method proposed in [12]. It is clearly observed that the BER difference between the optimal beamforming method proposed in [36], which require all CSI at all transmitting and receiving antennas, and the proposed method, which does not require CSI at any transmitting or receiving antenna, is just 3 dB. Note that the optimal difference between coherent and non-coherent method is 3 dB.




Figure 4. Performance comparison for relay transmission schemes using the AF protocol with 1 bpcu and $R=2$

4. CONCLUSION

This paper proposes a new cooperative communication system technique that operates in a bi-directional manner. The technique is validated through mathematical analysis and numerical simulations. Unlike existing methods, which require the availability of CSI at either the transmitter, receiver, or both, the proposed method eliminates the need for CSI at any transmitting or receiving antenna. The results demonstrate that the suggested cooperative communication system technique significantly enhances system performance, particularly in terms of BER, outperforming the current state-of-the-art methods.




REFERENCES

- [1] S. A. Aldalameh and D. Ciuonzo, "Distributed Detection Fusion in Clustered Sensor Networks Over Multiple Access Fading Channels," *IEEE Trans. on Signal and Inf. Process. Over Networks*, vol. 8, pp. 317–329, 2022, doi: 10.1109/TSIPN.2022.3161827.
- [2] C. E. C. Souza, R. Campello, C. Pimentel, and D. P. B. Chaves, "Chaos-Based Space-Time Trellis Codes With Deep Learning Decoding," *IEEE Trans. Circuits Syst. II*, vol. 68, no. 4, pp. 1472–1476, Apr. 2021, doi: 10.1109/TCSII.2020.3038481.
- [3] J. Joung, J. Choi, and B. C. Jung, "Double Space-Time Line Codes," *IEEE Trans. Veh. Technol.*, vol. 69, no. 2, pp. 2316–2321, Feb. 2020, doi: 10.1109/TVT.2019.2958666.
- [4] G. Zhang, X. Li, and X. Chen, "Multi-user High Rate Security Differential Chaos Shift Keying," in *2020 IEEE 20th International Conference on Communication Technology (ICCT)*, Nanning, China: IEEE, Oct. 2020, pp. 136–140, doi: 10.1109/ICCT50939.2020.9295950.
- [5] R. Alhamad and H. Boujemaa, "Symbol error probability of incremental relaying with distributed/centralized relay selection," *China Commun.*, vol. 17, no. 11, pp. 141–155, Nov. 2020, doi: 10.23919/JCC.2020.11.013.
- [6] M. M. Harb and M. F. Al-Mistarihi, "Dual Hop Differential Amplify-and-Forward relaying with selection combining cooperative diversity over Nakagami-m fading channels," *2016 8th IEEE International Conference on Communication Software and Networks (ICCSN)*, Beijing, China, 2016, pp. 225–228, doi: 10.1109/ICCSN.2016.7586654.
- [7] S. Alabed, I. Maaz, and M. Al-Rabayah, "Two-Phase Bidirectional Dual-Relay Selection Strategy for Wireless Relay Networks," *Computers, Materials & Continua*, vol. 69, no. 1, pp. 539–553, 2021, doi: 10.32604/cmc.2021.018061.




- [8] B. K. Jeemon and S. T. K., "Space Time Block Coded Vector OFDM with ML Detection," in *2021 8th International Conference on Smart Computing and Communications (ICSCC)*, Kochi, Kerala, India: IEEE, Jul. 2021, pp. 145–148, doi: 10.1109/ICSCC51209.2021.9528236.
- [9] H. J. Kwon, J. H. Lee, and W. Choi, "Machine Learning-Based Beamforming in Two-User MISO Interference Channels," in *2019 International Conference on Artificial Intelligence in Information and Communication (ICAIIIC)*, Okinawa, Japan: IEEE, Feb. 2019, pp. 496–499, doi: 10.1109/ICAIIIC.2019.8669027.
- [10] Z. Utkovski, G. Yammine, and J. Lindner, "A distributed differential space-time coding scheme for two-way wireless relay networks," in *2009 IEEE International Symposium on Information Theory*, 2009 IEEE International Symposium on Information Theory, Jun. 2009, pp. 779–783, doi: 10.1109/ISIT.2009.5205644.
- [11] S. Alabed, "Performance Analysis of Differential Beamforming in Decentralized Networks," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 8, no. 3, pp. 1692–1700, Jun. 2018, doi: 10.11591/ijece.v8i3.pp1692-1700.
- [12] V. Havary-Nassab, S. Shahbazpanahi, and A. Grami, "Joint Receive-Transmit Beamforming for Multi-Antenna Relaying Schemes," *IEEE Transactions on Signal Processing*, vol. 58, no. 9, pp. 4966–4972, Sep. 2010, doi: 10.1109/TSP.2010.2051431.
- [13] Y. Jing and H. Jafarkhani, "Distributed differential space-time coding for wireless relay networks," *IEEE Transactions on Communications*, vol. 56, no. 7, pp. 1092–1100, Jul. 2008, doi: 10.1109/TCOMM.2008.060388.
- [14] S. Alabed, M. Pesavento, and A. Klein, "Non-coherent distributed space-time coding techniques for two-way wireless relay networks," *Signal Processing*, vol. 93, no. 12, pp. 3371–3381, Dec. 2013, doi: 10.1016/j.sigpro.2012.12.001.
- [15] C. Xu *et al.*, "Finite-Cardinality Single-RF Differential Space-Time Modulation for Improving the Diversity-Throughput Tradeoff," *IEEE Trans. Commun.*, vol. 67, no. 1, pp. 318–335, Jan. 2019, doi: 10.1109/TCOMM.2018.2869812.
- [16] C. Zhai, Y. Li, X. Wang, L. Zheng, and C. Li, "Heterogeneous Non-Orthogonal Multiple Access With Distributed Alamouti Space-Time Coding," *IEEE Trans. Veh. Technol.*, vol. 70, no. 5, pp. 4796–4808, May 2021, doi: 10.1109/TVT.2021.3074189.
- [17] M. Shehadeh and F. R. Kschischang, "Space-Time Codes From Sum-Rank Codes," *IEEE Trans. Inform. Theory*, vol. 68, no. 3, pp. 1614–1637, Mar. 2022, doi: 10.1109/TIT.2021.3129767.
- [18] H. Murata, A. Kuwabara, and Y. Oishi, "Distributed Cooperative Relaying Based on Space-Time Block Code: System Description and Measurement Campaign," *IEEE Access*, vol. 9, pp. 25623–25631, 2021, doi: 10.1109/ACCESS.2021.3057618.
- [19] B. K. Jeemon and S. T. Kassim, "Design and Analysis of a Novel Space-Time- Frequency Block Coded Vector OFDM Scheme Robust to Rayleigh Fading," in *2020 IEEE 17th India Council International Conference (INDICON)*, New Delhi, India: IEEE, Dec. 2020, pp. 1–5, doi: 10.1109/INDICON49873.2020.9342086.
- [20] G. S. Rajan and B. S. Rajan, "Multigroup ML Decodable Collocated and Distributed Space-Time Block Codes," *IEEE Trans. Inform. Theory*, vol. 56, no. 7, pp. 3221–3247, Jul. 2010, doi: 10.1109/TIT.2010.2048475.
- [21] Y.-F. Hou and T.-M. Wu, "Modulation-Based Detect-and-Forward Relaying in Noncoherent UWB Systems," in *2018 IEEE 88th Vehicular Technology Conference (VTC-Fall)*, Chicago, IL, USA: IEEE, Aug. 2018, pp. 1–5, doi: 10.1109/VTCFall.2018.8690680.
- [22] S. Li, J.-K. Zhang, and X. Mu, "Noncoherent Massive Space-Time Block Codes for Uplink Network Communications," *IEEE Trans. Veh. Technol.*, vol. 67, no. 6, pp. 5013–5027, Jun. 2018, doi: 10.1109/TVT.2018.2815981.
- [23] M. Kanthimathi, R. Amutha, and B. N., "Performance Analysis of Multiple-Symbol Differential Detection based Space-Time Block Codes in Wireless Sensor Networks," in *2019 International Conference on Vision Towards Emerging Trends in Communication and Networking (ViTECoN)*, Vellore, India: IEEE, Mar. 2019, pp. 1–6, doi: 10.1109/ViTECoN.2019.8899684.
- [24] M. Wang, C. Hao, X. Dang, and X. Yu, "Non-coherent multi-symbol detection of PR-CPM for deep space relay satellites with physical-layer network coding," *China Commun.*, vol. 17, no. 7, pp. 101–112, Jul. 2020, doi: 10.23919/JCC.2020.07.009.
- [25] K. M. Attiah, K. Seddik, and R. H. Gohary, "Differential Unitary Space-Time Constellations From Spherical Codes," *IEEE Wireless Commun. Lett.*, vol. 9, no. 11, pp. 1909–1913, Nov. 2020, doi: 10.1109/LWC.2020.3007915.
- [26] S. Li, J.-K. Zhang, and X. Mu, "Double Full Diversity Massive Unitary Space-Time Codes for MIMO Channels," *IEEE Trans. Veh. Technol.*, vol. 68, no. 4, pp. 3686–3701, Apr. 2019, doi: 10.1109/TVT.2019.2900403.
- [27] B. M. Hochwald and W. Sweldens, "Differential unitary space-time modulation," *IEEE Trans. Commun.*, vol. 48, no. 12, pp. 2041–2052, Dec. 2000, doi: 10.1109/26.891215.
- [28] J. Zhen, S. Li, J.-K. Zhang, and K. M. Wong, "Design of Optimal Unitary Constellation with Noncoherent ML Receiver," in *2019 IEEE Pacific Rim Conference on Communications, Computers and Signal Processing (PACRIM)*, Victoria, BC, Canada: IEEE, Aug. 2019, pp. 1–5, doi: 10.1109/PACRIM47961.2019.8985123.
- [29] M. K. Simon and M.-S. Alouini, *Digital Communication Over Fading Channels*. New York, USA: John Wiley & Sons, Inc., 2000, doi: 10.1002/0471200697.
- [30] Q. Luo, S. S. Gao, W. Liu, and C. Gu, *Low-cost Smart Antennas*, in Microwave and Wireless Technologies Series, Wiley, 2019.
- [31] M. A. Hassanien, R. Hahnel, and D. Plettemeier, "Wideband Rotman Lens Beamforming Technique for 5G Wireless Applications," in *2019 2nd International Conference on Computer Applications & Information Security (ICCAIS)*, Riyadh, Saudi Arabia: IEEE, May 2019, pp. 1–5, doi: 10.1109/CAIS.2019.8769475.
- [32] T. Himsoon, W. P. Siri Wongpairat, W. Su, and K. J. R. Liu, "Differential Modulations for Multinode Cooperative Communications," *IEEE Trans. Signal Process.*, vol. 56, no. 7, pp. 2941–2956, Jul. 2008, doi: 10.1109/TSP.2008.917358.
- [33] S. Alabed, N. Mostafa, W. H. F. Aly, and M. Al-Rabayah, "A low complexity distributed differential scheme based on orthogonal space time block coding for decode-and-forward wireless relay networks," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 13, no. 1, pp. 1180–1188, Feb. 2023, doi: 10.11591/ijece.v13i1.pp1180-1188.
- [34] S. Han, P. Zhang, F. Shi, D. Cao, and F.-Y. Wang, "Low-complexity detection for multi-antenna differential unitary space-time modulation systems," in *2017 IEEE/CIC International Conference on Communications in China (ICCC)*, Qingdao: 2017 IEEE/CIC International Conference on Communications in China (ICCC), Oct. 2017, pp. 1–5, doi: 10.1109/ICCCChina.2017.8330463.
- [35] M. K. Singh, S. I. Amin, S. A. Imam, V. K. Sachan, and A. Choudhary, "A Survey of Wireless Sensor Network and its types," in *2018 International Conference on Advances in Computing, Communication Control and Networking (ICACCCN)*, Greater Noida (UP), India: IEEE, Oct. 2018, pp. 326–330, doi: 10.1109/ICACCCN.2018.8748710.
- [36] S. Alabed, M. Al-Rabayah, and W. Hosny, "A Beamforming Technique Using Rotman Lens Antenna for Wireless Relay Networks," *CMC*, vol. 73, no. 3, pp. 5641–5653, 2022, doi: 10.32604/cmc.2022.030371.
- [37] P. Deshpande and M. S. Madankar, "Techniques improving throughput of wireless sensor network: A survey," in *2015 International Conference on Circuits, Power and Computing Technologies [ICCPCT-2015]*, Nagercoil, India: IEEE, Mar. 2015, pp. 1–5, doi: 10.1109/ICCPCT.2015.7159430.

BIOGRAPHIES OF AUTHORS






Samer Alabed    is currently an associate professor and the head from Department of Biomedical Engineering at the German Jordanian University, Jordan. He was an associate professor of Electrical Engineering at the College of Engineering and Technology in the American University of the Middle East, Kuwait, from 2015 to 2022. He also worked in Darmstadt University of Technology, Darmstadt, Germany, from 2008 to 2015. He received his Ph.D. degree in Electrical Engineering and Information Technology from Darmstadt University of Technology, Germany. During the last 18 years, he has worked as an associate professor, assistant professor, researcher, and lecturer in several universities and supervised tens of master students and Ph.D. students. He received several awards and grants from IEE, IEEE, DAAD, DFG, ERC, EU, and AUM. He was invited to many conferences in Europe, US, and North Africa. Further information is available on his homepage: <http://drsamerlabed.wixsite.com/samer>. He can be contacted at email: Samer.Alabed@gju.edu.






Amer Alsaraira    holds a Ph.D. in Biomedical Engineering from Monash University since the year 2009. He is currently an assistant professor at Department of Biomedical Engineering, German Jordanian University, Jordan since 9/2022. He also worked as an assistant professor at the Department of Electrical Engineering, American University of Middle East (AUM), Kuwait, for the period between 8/2019-9/2022 and worked as an assistant professor at Department of Biomedical Engineering, Hashemite University, Jordan for the period between 12/2009 and 9/2019. He is teaching various courses for the undergraduate students, supervising their graduation projects, supervised undergraduate students, and a member of many committees at the department. He participated in many training workshops to support the university efforts toward gaining ABET accreditation. His current research is in the fields of modeling and simulation of biomedical systems, wireless networks, and DSP. He can be contacted at email: Amer.Alsaraira@gju.edu.jo.






Nour Mostafa    received a Ph.D. degree from the Queen's University Belfast School of Electronics, Electrical Engineering and Computer Science, UK, in 2013. He previously worked as a software developer with Liberty Information Technology, USA/UK, and is currently an associate professor of Computer Science in the College of Engineering and Technology, American University of the Middle East. His current research interests include grid computing, large database management, artificial intelligence, machine learning, distributed computing, cloud, fog, and IoT computing. He has authored and co-authored many refereed journal articles, conference papers, and book chapters. He is an active reviewer for many reputed international and IEEE journals and letters. Also, he has been selected as an international steering committee member of many conferences, and he has joined the editorial board of international journals. He can be contacted at email: Nour.Moustafa@aum.edu.kw.






Mohammad Al-Rabayah    holds a Ph.D. in Electrical Engineering from the University of New South Wales since 2011. He is currently an assistant professor at the American University of Middle East, Kuwait, since 2018. He is teaching various courses for the undergraduate students, an academic advisor for electrical engineering students, and a member of many committees for maintaining high level of education and research at the department. Al-Rabayah also worked as an assistant professor at Prince Sultan University, Riyadh-KSA, from 8/2015 to 8/2018. During his time, he taught many courses at the Department of Communications and Networks and participated to support the university efforts toward gaining ABET accreditation. He worked as an assistant professor at Prince Sattam bin Abdulaziz University, Al-Kharj, Arab Saudi, from 10/2014 to 6/2015. His current research is in the fields of wireless networks, and cooperative wireless communications. He can be contacted at email: Mohammad.Alrabayah@aum.edu.kw.






Ahmed Shdefat    received a Ph.D. degree from the Department of Software Engineering, Inje University School of Engineering, South Korea, in 2018. He was previously a research assistant in the Department of Software Engineering, Inje University, South Korea, and is currently an assistant professor of Computer Science in the College of Engineering and Technology, American University of the Middle East. His current research interests include IoT infrastructure and architecture, ECG signal processing, bioinformatics, real-time processing, human activities recognition, and E-health systems. He can be contacted at email: Ahmed.shdefat@aum.edu.kw.






Chamseddine Zaki    received a master's degree in Computer Science from the École Polytechnique de Nice-Sophia Antipolis in 2007. He received his Ph.D. degree in Computer Engineering from Centrale Nantes in 2011. He is currently an assistant professor in the American University of the Middle East, Kuwait. He has published more than 25 conference and journal papers in the fields of geographic information systems, spatiotemporal data analysis, multicriteria analysis, conceptual modeling, and travel time estimation. He can be contacted at email: Chamseddine.Zaki@aum.edu.kw.



Omar A. Saraereh    received the B.S. degree in Telecommunication Engineering from Mutah University, Jordan, in 1999, the M.Sc. degree in Digital Communication Systems in U.K., and the Ph.D. degree in Electrical and Electronic Engineering from Loughborough University, U.K., in 2005. From 2001 to 2005, he was a member of staff with the Centre for Mobile Communication Research, Loughborough University. He has more than 17 years of academic and practical experience in electrical engineering, mobile communications, various antennas design, fabrication and measurements, radiation hazards and health effects, and wireless communications. He was a high-level consultant and a turnkey solution originator in countless business and charitable sectors, and an international public speaker and a trainer on a variety of business and people management topics. He is currently a full professor with the Department of Electrical Engineering, Hashemite University, Jordan. He has published many articles in various international journals and conferences. He can be contacted at email: eloas2@hu.edu.jo.



Zakwan Al-Arnaout    received a Ph.D. degree from the School of Engineering and Computer Science at Victoria University of Wellington, Wellington, New Zealand. He is currently working as an assistant professor and department chair of the IST/TNT Department of the American University of the Middle East, Kuwait. His research interests include content caching and replication, multi-hop wireless networks, detection and prevention of distributed denial of service attacks, and key management schemes in WSNs. He is a member of the IEEE and the IEEE Computer Society. He can be contacted at email: Zakwan.AlArnaout@aum.edu.kw.